Case **Erector**





Features:

- Carton erecting, vertical forming, bottom flaps folding and bottom tape sealing automatically
- Carton erecting by air cylinder
- Working speed depends on carton dimensions
- Alarm when lacks tape or carton
- It can be easily adjusted to fit for cartons of varying sizes

Key Components:

- Motor brand: "GPG" of Taiwan
- Belt brand: "Yongli" of China
- Cylinder brand: Festo of Germany
- Contactor brand: "Schneider"
 of France
- Button switch brand: "Siemens APT" of Germany

Specifications:

- Carton size: 600 x 400 x 400mm
- Working speed: 8-10 boxes/min
- Apply tape: W48 -72mm
- Power supply: 400W
- Air pressure: 6kgf/cm², 450nl/min
- Machine size: L2050xW1950xH1450mm
- Shipping size: L2230xW1450x 1580mm
- Machine weight: 400kg
- Photoelectric switch brand: "P+F" of Germany
- Touch screen brand: handled by customer
- PLC brand: handled by customer
- Vacuum generator brand:"SMC" of Japan
- Power switch brand: "Schneider" of France

CO Usage / Application

FOOD, SPICES, DAIRY, PHARMA, ICE CREAM, COLD STORAGE AND WAREHOUSES

Disclaimer: The specifications and image provided in this product catalog are general and subject to variation based on specific customer requirements. Changes may occur without prior intimation. For precise details, please refer to the technical layout provided with offer for exact specifications.

Case Sealer



Features:

- Motor brand: "GPG" of Taiwan
- Belt brand: "Yongli" of China
- Cylinder brand: Festo of Germany
- Contactor brand: "Schneider" of France
- Button switch brand: "Siemens APT" of Germany
- Power switch brand: "Schneider" of France
- Photoelectric switch brand: "P+F" of Germany
- Vacuum generator brand: "SMC" of Japan

Key Components:

- Side belts driven
- Automatically flaps folding top covers
- Sealing top and bottom at the same time
- Manually adjust the height and width for sealing varying carton sizes.

Disclaimer: The specifications and image provided in this product catalog are general and subject to variation based on specific customer requirements. Changes may occur without prior intimation. For precise details, please refer to the technical layout provided with offer for exact specifications.

Specifications:

- Belt speed: 20m/min (10 15 boxes /min)
- Box size: 600 x 500 x 500mm
- Apply tape: W48-72mm
- Power supply: 220/380V 50Hz
- Power output: 200w
- Air pressure: 6kgf/cm², 40nl/min
- Machine size: L1700 x W930 x H1510mm
- Shipping size: L1760 x W1040 x H1550mm
- Machine weight: 200kg
- · Machine guarded by acrylic barriers from both sides

CO Usage / Application

FOOD, SPICES, DAIRY, PHARMA, ICE CREAM, COLD STORAGE AND WAREHOUSES